

Products and techniques for construction and chemical industry

# **PC<sup>®</sup> ECOCLEAN**

## **Ecological Cleaning Solvent**

### 1. Description

**PC**<sup>®</sup> **Ecoclean** is a mixture of sulphide acid esters

### 2. Application

- Cleaning of injection and spraying equipment.
- Removal of non-reacted polyurethane and epoxy resin.

#### 3. Properties

- Rinsing agent with a high cleansing property for polyurethanes
- Replaces acetone, methylene chloride and other organic solvents
- Low vapour pressure at room temperature
- Non toxic

#### 4. Application

Clean the apparatus thoroughly with the pure PC<sup>®</sup> Ecoclean

#### 5. Consumption

Depends on the application and the pump.

#### 6. Characteristics

- Colour : light yellow liquid
- Density (20°C) : 1,05 kg/l
- High flash point : ~ 225° C

#### 7. Packaging

Standard packaging: jerry cans of 10 kg.

#### 8. Shelf life

Minimum 1 year.

#### 9. Precautions and security measures

- Avoid contact with the skin and eyes;
- Wear appropriate clothing, gloves and safety glasses;
- More information on the Safety Material Data Sheet.

#### Date: 31/01/08

PC ECOCLEAN TD

Page 1 of 1

This information is given to our best knowledge. It is offered as a possible helpful suggestion in experimentation you may care to make along these lines. It is subject to revision as additional knowledge and experimentation are gained. We make no guarantee of results and assume no obligation or liability whatsoever in connection with this information

CHNICAL DATASHEET

Terbekehofdreef 50-52 B-2610 Wilrijk

phone +32 3 828.94.95 fax +32 3 830.27.69

info@tradecc.be www.tradecc.be