

DECOQUARZ

SURFACE HARDENER FOR STAMPED FLOORS

DESCRIPTION

DECOQUARZ Is a mixture of mineral aggregates. **HARD NATURAL** especially used in the making of monolithic stamped floors..

PACKAGING

DECOQUARZ Is packed in very resistant paper bags. 33 kg. On request it is possible also 25 kg.

STORAGE

12 months in properly stored unopened dry clean area.

ADVANTAGES

Ready to use, pre mixed with cement and additives . applied manually in the dry shake and in the topping method. It's high mechanical resistance make it a perfect solution on heavily traffic areas, Does not oxide. It can have a smooth or anti skid finish.

It abides with fire safety regulations. Treated with **METALCRIL** as great resistance to the weather , frost and de frosting salts.

It is possible to obtain different shades

TECHNICAL DATA

CARATTERISTICHE CHIMICO - FISICHE	
Colore (al naturale)	bianco - giallo sedimentaria metamorfica
Origine	metamorfica
Granulometria	0.50-0.70-1-2-3
P.A.F.	0, 2%
Durezza scala Mohs	6° - 7°

MECHANICAL RESISTANCES

TESTS		
Tensile Resis	7 gg – Mpa 7,62	28 gg Mpa 7,29
Compressi on Resis	7 gg – Mpa 47,30	28gg Mpa 67,50
Abrasion Resis	BHOME EN 13813 A 9	A 9
Abrasion Resis	WHELL EN 1339 ANNEX G	I
Marcatura CE DECOQUARZ		
06		
EN 13813 CT-C70-F9 –A9-I		



WHERE TO USE

DECOQUARZ is used in home and industrial floors –high traffic-, garages, parks, ramps
Market area shopping malls

- **CURING**
- Light traffic 7 days
- Everyday traffic 28 days

PRECAUTIONS

Keep out reach of children. Avoid contact with eyes. Wear suitable gloves. Wear suitable protective clothing . Do not breathe dust. In case of insufficient ventilation. Wear suitable respiratory equipment. Wash soiled clothing before reuse.

FIRST AID

Wash exposed skin with soap and water. Flush eyes with large quantities of water. If breathing is difficult, move person to fresh air.

WASTE DISPOSAL METHOD

Dispose of this product in a landfill, in accordance with local regulations.