

DECOSTAMP

POWDER RELEASE AGENT USED FOR DECORATIVE FLOORING

DESCRIPTION

DECOSTAMP a dry mixed ready to use Release Agent, An especially studied formula to simplify the distribution on fresh concrete surfaces.

PACKAGING

15 KG plastic containers

STORAGE

One year in properly stored unopened container in a dry clean area

ADVANTAGES

A carbonate formulated Release Agent with natural and synthetic iron oxides resistant to sun rays UV. And other aggregates that permit the achievement an even and high quality product. It belongs to **DECOSTAMP** specific for the stamped floors product line. It is used together and only with **DECOQUARTZ**. See the technical data sheet.

WHERE TO USE

DECOSTAMP Release agent is normally used in the making of printed and/or decorative cement flooring. The functions of this product are two: the first to create an impalpable layer in order to separate the **DECOSTAMP** mould from the fresh cement, secondly to add a second colour to the surface already coloured by the **DECOQUARZ DECOSTAMP**, hereby giving the flooring a natural shading. It is a non-stick, releasing, coloured waterproof powder which is distributed on the surface already treated with **DECOQUARZ DECOSTAMP** and enables the printing in the desired shape.

WARNING: Do not use Calcium Chloride or Calcium Chloride based products where coloured cement is present.

APPLICATION

The release agent is specially formulated to produce **DECOSTAMP** printed flooring and is used together with **DECOQUARZ** and **METALCRIL 12-20 Sealer**.

After having applied **DECOQUARZ**(see data) and immediately before proceeding with printing, one applies a veil of **DECOSTAMP** which must be applied by sprinkling method in minimum quantities. Consume: Approximately 7-8sqm/kg of **DECOSTAMP**. See the data sheets: **DECOQUARZ** and Sealer **DECOSTAMP** and **METALCRIL**.

COLOURS

DECOSTAMP is available in 15 standard colours visible in the **DECOSTAMP** colour chart. On request and for large quantities (1500kg) it's possible to order personalized shades.

STORAGE, EXPIRY AND GUARANTEE

DECOSTAMP is packed in plastic buckets, to protect the product from external agents and humidity and allowing it to be closet hermetically so

that the product remains unaltered until use. **DECOSTAMP** is guaranteed for 12 months when stored correctly in it's original containers, in a dry place.

DECOSTAMP is not responsible for eventual problems derived from it's application on other products which are not produced by us. Apse s.r.l. is not responsible for damage sustained during transport. ..

PRECAUTIONS

Keep out reach of children. Avoid contact with eyes. Wear suitable gloves. Wear suitable protective clothing . Do not breathe dust. In case of insufficient ventilation. Wear suitable respiratory equipment. Wash soiled clothing before reuse.

FIRST AID

Wash exposed skin with soap and water. Flush eyes with large quantities of water. If breathing is difficult, move person to fresh air.

WASTE DISPOSAL METHOD

Dispose of this product in a landfill, in accordance with local regulations.