

TOPSEAL

FEATURES

- TOPSEAL is a top of the line concrete sealer composed of a high quality solvent based acrylic polymer that resists UV degradation.
- It effectively seals the concrete against water ingress and absorption protecting it from damage through carbon dioxide and chloride infusion.

APPLICATION

- Concrete
- Interior and exterior

Characteristics

- Color : Clear
- Spreading rate : 8 – 10 Sqm/Ltr (per coat)
- Gloss level : 75 – 85 %
- Specific gravity : 0.90
- Solids by Volume : 33% +/- 2%
- Diluent : Aromatic Solvents
- Flash point : 28°C
- Drying time (30°C) : 24 - 48 Hours (Ready for recoat after 24 Hours)

SURFACE PREPARATION

All surfaces must be free of dirt, oil, grease, moisture and other contaminants.

APPLICATION METHOD

Always ensure adequate ventilation during paint application for health and safety reasons and also to facilitate and speed up drying. Avoid humid conditions i.e., >95% when condensation is likely to interfere.

1. Dilution: Dilution is not required
2. Brush : Recommended in areas where spraying is not possible
3. Roller : Use on large flat surfaces when spraying is not recommended.

Apply a maximum of 1 mil (25microns) thickness per coat allowing the first coat to dry before applying the succeeding coat.

DISCLAIMER:

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.

STORAGE AND SHELF LIFE

Store under dry and cool conditions, up to 18 months in original sealed containers.

HANDLING

DISPOSAL: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Caution: It is strongly advised to keep used drums firmly closed in order to avoid skin formation on top.

SAFETY PRECAUTION

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Other industrial practices are applicable.

Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapor or spray.

MSDS is available on request for the safe handling of this product

FIRST AID

Eyes: in the event of accidental splashes, fluid eyes with warm water immediately and obtain medical advice.

Skin: wash skin thoroughly with soap and water or approved industrial cleaner.

DO NOT USE solvent or thinners.

Inhalation: remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INCLUDE VOMITING, obtain immediate medical attention.

DISCLAIMER:

The information contained in this datasheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about the product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RAR RESIN Technical Service Department.