



OUR PRODUCTS

Choose collection

Ceiling decoration

Floor profiles

Lighting

Wall decoration

Decorative elements

Accessories

CHOOSE YOUR LANGUAGE

English



Your are here: > [Accessories](#) > FX200 DecoFix Extra
[Home](#)

Accessories

- Show all
- Adhesives
- Installation tools
- Sales & marketing tools

SEARCH BY:

COLLECTION

- Luxxus
- Axxent
- Basixx

SOLUTION



FX200 DecoFix Extra




Adhesives

Adhesive for perfect jointing.
 For seam joints between the mouldings. Push the profiles strongly to each other and remove excess of DecoFix Extra preferably before hardening (wait at least two hours) with acetone or Synth Thinner. The adhesive can be painted after 24 hrs.
 310ml > min. 80m.
 The correct use of DecoFix glues is very important:

- For Axxent and Luxxus profiles you should use DecoFix Pro for indoor spaces and on porous surfaces you should use DecoFix Extra for the seams. Use DecoFix Hydro on new build or on recently plastered walls, for outdoor applications and non-porous surfaces.

- For Basixx profiles use the DecoFix Pro glue for installation and to seam joints.





OUR PRODUCTS

Choose collection

Ceiling decoration

Floor profiles

Lighting

Wall decoration

Decorative elements

Accessories

CHOOSE YOUR LANGUAGE

English



Your are here: [Home](#) > [Accessories](#) > FX210 DecoFix Extra

Accessories

- Show all
- Adhesives
- Installation tools
- Sales & marketing tools

SEARCH BY:

COLLECTION

- Luxxus
- Axxent
- Basixx

SOLUTION



FX210 DecoFix Extra



Adhesives

Adhesive for perfect jointing.
 For seam joints between the mouldings. Push the profiles strongly to each other and remove excess of DecoFix Extra preferably before hardening (wait at least two hours) with acetone or Synth Thinner. The adhesive can be painted after 24 hrs.
 80ml > min. 20m
 The correct use of DecoFix glues is very important:

- For Axxent and Luxxus profiles you should use DecoFix Pro for indoor spaces and on porous surfaces you should use DecoFix Extra for the seams. Use DecoFix Hydro on new build or on recently plastered walls, for outdoor applications and non-porous surfaces.

- For Basixx profiles use the DecoFix Pro glue for installation and to seam joints.

